
# VISO TALIS CURVE

**36 variants**



### Dimensions




### Available colours

**Nickel** **Uncoloured**

VISO TALIS CURVE is a luminaire on a curved slim stem with a disc-shaped head. The construction is made of brass. The light source is an integrated LED module. The protection rating is IP65. The impact rating is IK05.

**LUMINAIRE POWER**

5.5 - 8.2 W

**LUMINAIRE LUMINOUS FLUX**

311 - 477 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of VISO TALIS CURVE.

| | | | |
|---|---|---|---|
| Mounting position | **Bollard** | Power factor | **0.96** |
| Housing | **Brass** | Protection rating | **IP65 / IK05** |
| Optic | **Plastic** | Insulation class | **Class III** |
| Light source | **H.P. LED** | Lifetime | **>60.000h L80B10@35°C** |
| Body dimensions | **Ø 105 × 1012 mm** | Operating temperature | **-20…+45°C** |
| Control Gear | **Remote Electronic Driver** | Operating humidity | **5…95%** |
| Colour uniformity | **3 SDCM** | Lighting direction | **Downwards** |
| Ripple | **3** | Accessories | **CONNECTION BOX** |
| Operating voltage | **3 V** | | |

**Markings and catalogue references** **CE • LM80 • LM79 • TM21 • REACH**

## Options per version

**Beams 117° (VW) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 52.7 - 64.7 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **927** | 2700 K | 117° | 5.5 - 8.2 | **311 - 432** |
| **930** | 3000 K | 117° | 5.5 - 8.2 | **322 - 443** |
| **940** | 4000 K | 117° | 5.5 - 8.2 | **356 - 477** |

### Luminous flux range per version

Minimum 311 lm / 5.5 W / 927 / BO0065CL109ON

Maximum 477 lm / 8.2 W / 940 / BO0070CL109ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >