
VILLA FAROS

48 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

LUMINAIRE POWER

18 - 30 W

LUMINAIRE LUMINOUS FLUX

1,710 - 3,000 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VILLA FAROS.

Mounting position	**Pole Mounted**	Ripple	**3**
Housing	**Inox**	Operating voltage	**3 V**
Optic	**Lens**	Power factor	**0.96**
Light source	**H.P. LED**	Protection rating	**IP40 / IK02**
Body dimensions	**350 × 350 × 470 mm**	Operating humidity	**5…95%**
Control Gear	**Built-in ECG**	Lighting direction	**Downwards**
Colour uniformity	**3 SDCM**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 104° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 95 - 100 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	104°	18 - 30	**1,710 - 2,850**
940	4000 K	104°	18 - 30	**1,800 - 3,000**

Luminous flux range per version

Minimum 1,710 lm / 18 W / 930 / AM0353CL001ON

Maximum 3,000 lm / 30 W / 940 / AM0356CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >