
ARBOR FOCUS

324 variants



Dimensions



Available colours

Nickel **Colourless** **Black stainless steel**

ARBOR FOCUS is an outdoor LED spotlight. The body has a diameter of 30 mm and length of 62 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. The light source is an integrated high-power LED module. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The head offers vertical adjustment through 90°. The construction combines a brass body with a flexible mounting strap. A glass lens forms the optical exit of the lighting unit. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. Versions are available with CRI80 at 2700, 3000 and 4000 K and CRI90 at 2700, 3000 and 4000 K. It is available in black stainless steel, nickel and unpainted finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP67 with an impact rating of IK07.

LUMINAIRE POWER

1.1 - 1.6 W

LUMINAIRE LUMINOUS FLUX

113 - 184 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of ARBOR FOCUS.

Mounting position	**Ceiling, Wall Mounted, Floor**	Ripple	**3**
Housing	**Brass, Rubber**	Power factor	**0.96**
Optic	**Glass Lens**	Protection rating	**IP67 / IK07**
Light source	**H.P. LED**	Insulation class	**Class III**
Body dimensions	**Ø 30 mm**	Lifetime	**>50.000h L80B10**
Control Gear	**Remote Electronic Driver**	Lighting direction	**Sideways**
Colour uniformity	**3 SDCM**	Accessories	**CONNECTION BOX 1**

Markings and catalogue references **CE • LM80**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.3 - 121.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
827	2700 K	8°, 25°, 45°	1.1 - 1.6	**118 - 164**
830	3000 K	8°, 25°, 45°	1.1 - 1.6	**124 - 172**
840	4000 K	8°, 25°, 45°	1.1 - 1.6	**136 - 184**
927	2700 K	8°, 25°, 45°	1.1 - 1.6	**113 - 156**
930	3000 K	8°, 25°, 45°	1.1 - 1.6	**118 - 164**
940	4000 K	8°, 25°, 45°	1.1 - 1.6	**130 - 176**

Luminous flux range per version

Minimum 113 lm / 1.1 W / 927 / PJ0214CL151ON

Maximum 184 lm / 1.6 W / 840 / PJ0229CL151ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >