
# BELL TALIS 30

**60 variants**



## Dimensions




## Available colours

**White** **Black** **Grey** **Gold** **Chrome green**

BELL TALIS 30 is an outdoor LED wall luminaire made of aluminium. The lighting section has height 63 mm and diameter 300 mm. Wall mounting adds light at entrances, paths beside buildings and exterior walls. The arrangement of fittings can follow the rhythm of the facade and its access points. The light source is an integrated high-power LED module. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in chrome green, black, white, grey and gold finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK04.

**LUMINAIRE POWER**

3.1 - 4.7 W

**LUMINAIRE LUMINOUS FLUX**

166 - 246 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of BELL TALIS 30.

| | | | |
|---|---|---|---|
| Mounting position | **Wall Mounted** | Ripple | **3** |
| Housing | **Aluminium** | Operating voltage | **230 V** |
| Light source | **H.P. LED** | Power factor | **0.96** |
| Body dimensions | **Ø 300 × 63 mm** | Protection rating | **IP65 / IK04** |
| Control Gear | **Built-in ECG** | Lighting direction | **Downwards** |

| | |
|---|---|
| **Markings and catalogue references** | **CE** |

## Options per version

**Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 48.8 - 58.2 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **930** | 3000 K | | 3.1 - 4.7 | **166 - 229** |
| **940** | 4000 K | | 3.1 - 4.7 | **182 - 246** |

### Luminous flux range per version

Minimum 166 lm / 3.1 W / 930 / WF0241CL140ON

Maximum 246 lm / 4.7 W / 940 / WF0244CL140ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr >**