CONCRETE CONTO 2M

24 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

CONCRETE CONTO 2M is an LED lighting bollard made of concrete and aluminium. The body has a length of 230 mm, width of 105 mm and height of 690 mm. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. The construction is rated IP65 with an impact rating of IK07.

LUMINAIRE POWER

4.2 - 6.3 W

LUMINAIRE LUMINOUS FLUX

232 - 356 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of CONCRETE CONTO 2M.

Mounting position	**Bollard**	Operating voltage	**230 V**
Housing	**Concrete**	Power factor	**0.96**
Optic	**Safety Glass Sandblast**	Protection rating	**IP65 / IK07**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10**
Body dimensions	**105 × 230 × 690 mm**	Lighting direction	**Sideways**
Ripple	**3**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Luminous efficacy 51.8 - 63.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		4.2 - 6.3	**232 - 324**
930	3000 K		4.2 - 6.3	**240 - 332**
940	4000 K		4.2 - 6.3	**264 - 356**

Luminous flux range per version

Minimum 232 lm / 4.2 W / 927 / BO0130CL009

Maximum 356 lm / 6.3 W / 940 / BO0135CL009

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >