# FAMA ASYMMETRIC

**90 variants**



### Dimensions




### Available colours

**White** **Black** **Grey** **Nickel** **Colourless**

FAMA ASYMMETRIC is a recessed LED wall luminaire made of brass. The body has a diameter of 35 mm and height of 37 mm. Its recessed installation keeps the body within the wall and leaves the light opening visible. It suits paths, entrances and surfaces where lighting needs to form part of the architecture. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white, grey, nickel and unpainted finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP67 with an impact rating of IK07.

**LUMINAIRE POWER**

## 1 - 1.6 W

**LUMINAIRE LUMINOUS FLUX**

## 29 - 45 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of FAMA ASYMMETRIC.

| | | | |
|---|---|---|---|
| Mounting position | **Wall Recessed** | Ripple | **3** |
| Housing | **Brass** | Power factor | **0.96** |
| Optic | **Safety Glass Clear** | Protection rating | **IP67 / IK07** |
| Light source | **H.P. LED** | Lifetime | **>50.000h L80B10** |
| Body dimensions | **Ø 35 × 37 mm** | Lighting direction | **Sideways** |
| Control Gear | **Remote Electronic Driver** | Accessories | **FAMA BOX, LED DRIVER** |
| Colour uniformity | **3 SDCM** | | |
| **Markings and catalogue references** | **CE • LM80** | | |

## Options per version

**Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 26.3 - 31.7 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **927** | 2700 K | | 1 - 1.6 | **29 - 41** |
| **930** | 3000 K | | 1 - 1.6 | **30 - 42** |
| **940** | 4000 K | | 1 - 1.6 | **33 - 45** |

### Luminous flux range per version

Minimum 29 lm / 1 W / 927 / WF0245CL002ON

Maximum 45 lm / 1.6 W / 940 / WF0250CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr >**