FAMA L GROUND LED

18 variants



Dimensions



Available colours

Inox

FAMA L GROUND LED is a recessed LED ground luminaire made of stainless steel. The body has a diameter of 80 mm and height of 134 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. The finish is stainless steel. The construction is rated IP67 with an impact rating of IK08.

LUMINAIRE POWER

3.4 - 4.9 W

LUMINAIRE LUMINOUS FLUX

338 - 528 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FAMA L GROUND LED.

Mounting position	**Floor**	Ripple	**3**
Housing	**Inox**	Operating voltage	**230 V**
Optic	**Safety Glass Clear**	Power factor	**0.96**
Light source	**H.P. LED**	Protection rating	**IP67 / IK08**
Body dimensions	**Ø 80 × 134 mm**	Lifetime	**>50.000h L80B10 PAR16 / GU10 / 230V**
Control Gear	**Built-in ECG**	Lighting direction	**Upwards**
Colour uniformity	**3 SDCM**	Accessories	**CONNECTION BOX**

Markings and catalogue references **CE • LM80**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off

Luminous efficacy 96.3 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	3.4 - 4.9	**338 - 468**
930	3000 K	8°, 25°, 45°	3.4 - 4.9	**355 - 492**
940	4000 K	8°, 25°, 45°	3.4 - 4.9	**391 - 528**

Luminous flux range per version

Minimum 338 lm / 3.4 W / 927 / GR0158CL135ON

Maximum 528 lm / 4.9 W / 940 / GR0173CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >