FAMA L OUT DZ LED

72 variants



Dimensions



Available colours

White **Black** **Grey** **Inox**

FAMA L OUT DZ LED is an LED lighting bollard made of stainless steel. The body has a diameter of 54 mm and height of 105 mm. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. The head offers vertical adjustment through 90°. The optical surface is made of clear safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white, grey and stainless steel finishes. The construction is rated IP64 with an impact rating of IK03.

LUMINAIRE POWER

3.4 - 4.9 W

LUMINAIRE LUMINOUS FLUX

338 - 528 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FAMA L OUT DZ LED.

Mounting position	**Bollard**
Housing	**Inox**
Optic	**Safety Glass Clear**
Light source	**H.P. LED**
Body dimensions	**Ø 54 × 105 mm**
Ripple	**3**

Power factor	**0.96**
Protection rating	**IP64 / IK03**
Lifetime	**>50.000h L80B10 PAR16 / GU10 / 230V**
Lighting direction	**Sideways**
Accessories	**NAIL DZ INOX 1000MM, NAIL DZ INOX 250MM, CONNECTION BOX**

Markings and catalogue references	**LM80**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off

Luminous efficacy 96.3 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	3.4 - 4.9	**338 - 468**
930	3000 K	8°, 25°, 45°	3.4 - 4.9	**355 - 492**
940	4000 K	8°, 25°, 45°	3.4 - 4.9	**391 - 528**

Luminous flux range per version

Minimum 338 lm / 3.4 W / 927 / BO0154CL002ON

Maximum 528 lm / 4.9 W / 940 / BO0169CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >