FAMA STEPS 2

90 variants



Dimensions



Available colours

White **Black** **Grey** **Nickel** **Uncoloured**

FAMA STEPS 2 is a recessed LED ground luminaire made of brass. The body has a diameter of 40 mm and height of 48 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white, grey, nickel and unpainted finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP67 with an impact rating of IK07.

LUMINAIRE POWER

1 - 1.6 W

LUMINAIRE LUMINOUS FLUX

7 - 11 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FAMA STEPS 2.

Mounting position	**Floor**	Ripple	**3**
Housing	**Brass**	Power factor	**0.96**
Optic	**Safety Glass Clear**	Protection rating	**IP67 / IK07**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10**
Body dimensions	**Ø 40 × 48 mm**	Lighting direction	**Sideways**
Control Gear	**Remote Electronic Driver**	Accessories	**FAMA BOX, LED DRIVER**
Colour uniformity	**3 SDCM**		
Markings and catalogue references	**CE • LM80**		

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 6.4 - 7.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		1 - 1.6	**7 - 10**
930	3000 K		1 - 1.6	**8 - 10**
940	4000 K		1 - 1.6	**8 - 11**

Luminous flux range per version

Minimum 7 lm / 1 W / 927 / GR0212CL002ON

Maximum 11 lm / 1.6 W / 940 / GR0217CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >