FERUS 80

81 variants



Dimensions



Available colours

White **Black** **Gold**

FERUS 80 is an LED reading light made of steel and aluminium. The lighting section has height 100 mm and diameter 25 mm. It is intended for local reading light in bedrooms, hotel rooms and seating areas. Positioning it close to the user brings light to the required area without having to change the lighting across the entire room. The light source is an integrated high-power LED module. The head offers vertical adjustment through 90° and horizontal adjustment through 360°. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white and gold finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK05.

LUMINAIRE POWER

4 W

LUMINAIRE LUMINOUS FLUX

209 - 249 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FERUS 80.

Mounting position	**Wall Mounted**	Control Gear	**Built-in ECG**
Housing	**Steel, Aluminium**	Operating voltage	**230 V**
Light source	**H.P. LED**	Protection rating	**IP20 / IK05**
Body dimensions	**Ø 25 × 100 mm**	Lighting direction	**Sideways**
Markings and catalogue references	**CE**		

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 52.3 - 62.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	4	**209**
930	3000 K	8°, 25°, 45°	4	**229**
940	4000 K	8°, 25°, 45°	4	**249**

Luminous flux range per version

Minimum 209 lm / 4 W / 927 / DER0400CL002ON

Maximum 249 lm / 4 W / 940 / DER0406CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >