# MINI TERES 1 BRASS DZ + TR + NAIL

**540 variants**



### Dimensions




### Available colours

**White** **Black** **Grey** **Anthracite** **Uncoloured**

MINI TERES 1 BRASS DZ + TR + NAIL is an LED spotlight on a mounting stem made of brass. The cylindrical head has a diameter of 60 mm and an axial length of 50 mm. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. The head offers vertical adjustment through 90° and horizontal adjustment through 360°. The optical surface is made of clear safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white, grey and unpainted finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK08.

**LUMINAIRE POWER**

## 1.1 - 4.9 W

**LUMINAIRE LUMINOUS FLUX**

## 113 - 528 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of MINI TERES 1 BRASS DZ + TR + NAIL.

| | |
|---|---|
| Mounting position | **Bollard** |
| Housing | **Brass** |
| Optic | **Safety Glass Clear** |
| Light source | **H.P. LED** |
| Body dimensions | **Ø 60 × 50 mm** |
| Control Gear | **Remote Electronic Driver** |
| Colour uniformity | **3 SDCM** |

| | |
|---|---|
| Ripple | **3** |
| Power factor | **0.96** |
| Protection rating | **IP65 / IK08** |
| Lifetime | **>50.000h L80B10 Module 3x H.P.LED CRI80 Ripple <3%** |
| Lighting direction | **Sideways** |
| Accessories | **BRASS NAIL, DZ M10** |

| | |
|---|---|
| **Markings and catalogue references** | **CE • LM80** |

## Options per version

**Beams 8° (UN), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 96.3 - 116.4 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **927** | 2700 K | 8°, 25°, 45° | 1.1 - 4.9 | **113 - 468** |
| **930** | 3000 K | 8°, 25°, 45° | 1.1 - 4.9 | **118 - 492** |
| **940** | 4000 K | 8°, 25°, 45° | 1.1 - 4.9 | **130 - 528** |

### Luminous flux range per version

Minimum 113 lm / 1.1 W / 927 / BO0226CL009ON

Maximum 528 lm / 4.9 W / 940 / BO0259CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr >**