MINI TERES 1 SPOT H.P.LED

540 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite** **Dark brown**

MINI TERES 1 SPOT H.P.LED is an outdoor LED spotlight made of aluminium. The body has a diameter of 60 mm and height of 50 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. The light source is an integrated high-power LED module. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The head offers vertical adjustment through 90°. The optical surface is made of clear safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in dark brown, anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK08.

LUMINAIRE POWER

1.1 - 4.9 W

LUMINAIRE LUMINOUS FLUX

113 - 528 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MINI TERES 1 SPOT H.P.LED.

Mounting position	**Ceiling, Wall Mounted, Floor, Amenity**
Housing	**Brass**
Optic	**Safety Glass Clear**
Light source	**H.P. LED**
Body dimensions	**Ø 60 × 50 mm**
Control Gear	**Remote Electronic Driver**
Colour uniformity	**3 SDCM**

Ripple	**3**
Power factor	**0.96**
Protection rating	**IP65 / IK08**
Lifetime	**>50.000h L80B10 Module 3x H.P.LED CRI80 Ripple <3%**
Lighting direction	**Sideways**
Accessories	**BRASS NAIL, CONNECTION TOOL 2, CONNECTION TOOL 3**

Markings and catalogue references	**CE • LM80**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.3 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	1.1 - 4.9	**113 - 468**
930	3000 K	8°, 25°, 45°	1.1 - 4.9	**118 - 492**
940	4000 K	8°, 25°, 45°	1.1 - 4.9	**130 - 528**

Luminous flux range per version

Minimum 113 lm / 1.1 W / 927 / PJ0325CL152ON

Maximum 528 lm / 4.9 W / 940 / PJ0358CL152ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >