
NEPA GROUND OUT BRASS LED

324 variants



Dimensions



Available colours

White | Black | Grey | Nickel | Anthracite | Colourless

NEPA GROUND OUT BRASS LED is a surface-mounted LED ground luminaire made of brass. The body has a diameter of 176 mm and height of 50 mm. It is installed at ground level to illuminate nearby surfaces, planting and architectural features. Its position determines which elements of the landscape receive emphasis. The light source is an integrated high-power LED module. The optical surface is made of sandblasted safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is offered in multiple finishes, including anthracite, black, white and grey. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP67 with an impact rating of IK10.

LUMINAIRE POWER

1.1 - 1.6 W

LUMINAIRE LUMINOUS FLUX

113 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NEPA GROUND OUT BRASS LED.

Mounting position	**Floor**	Control Gear	**Built-in ECG**
Housing	**Brass**	Power factor	**0.96**
Optic	**Sandblasted safety glass**	Protection rating	**IP67 / IK10**
Light source	**H.P. LED**	Lighting direction	**Upwards**
Body dimensions	**Ø 176 × 50 mm**		

Markings and catalogue references **CE**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.3 - 116.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	1.1 - 1.6	**113 - 156**
930	3000 K	8°, 25°, 45°	1.1 - 1.6	**118 - 164**
940	4000 K	8°, 25°, 45°	1.1 - 1.6	**130 - 176**

Luminous flux range per version

Minimum 113 lm / 1.1 W / 927 / GR0332CL001ON

Maximum 176 lm / 1.6 W / 940 / GR0347CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >