NEXUS DAMA LED

30 variants



Dimensions



Available colours

White **Black** **Grey** **Nickel** **Anthracite**

NEXUS DAMA LED is a recessed LED wall luminaire made of stainless steel and aluminium. The body has a length of 120 mm, width of 120 mm and height of 68 mm. Its recessed installation keeps the body within the wall and leaves the light opening visible. It suits paths, entrances and surfaces where lighting needs to form part of the architecture. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white, grey and nickel finishes. The construction is rated IP65 with an impact rating of IK06.

LUMINAIRE POWER

2.1 - 3.1 W

LUMINAIRE LUMINOUS FLUX

58 - 89 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NEXUS DAMA LED.

Mounting position	**Wall Recessed**	Power factor	**0.96**
Housing	**Stainless steel / Aluminium**	Protection rating	**IP65 / IK06**
Optic	**Safety Glass Clear**	Lifetime	**>50.000h L80B10**
Light source	**H.P. LED**	Lighting direction	**Sideways**
Body dimensions	**120 × 120 × 68 mm**	Accessories	**BOX NEXUS**
Ripple	**3**		
Markings and catalogue references	**CE • LM80**		

Options per version

Control On-Off

Luminous efficacy 25.9 - 31.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		2.1 - 3.1	**58 - 81**
930	3000 K		2.1 - 3.1	**60 - 83**
940	4000 K		2.1 - 3.1	**66 - 89**

Luminous flux range per version

Minimum 58 lm / 2.1 W / 927 / WF0263CL009ON

Maximum 89 lm / 3.1 W / 940 / WF0268CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >