
NINIO 2 H.P.LED

2,304 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

NINIO 2 H.P.LED is a linear LED facade luminaire made of PMMA. The body has a diameter of 60 mm. The range offers different lengths, from 630 to 2550 mm, to suit the layout of the space. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. The light source is an integrated high-power LED module. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The optical surface is made of clear PMMA. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 13x45° oval distribution provides elongated coverage for surfaces and routes with a matching geometry. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP68 with an impact rating of IK05.

LUMINAIRE POWER

11.2 - 68 W

LUMINAIRE LUMINOUS FLUX

1,128 - 7,392 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NINIO 2 H.P.LED.

Mounting position	**Ceiling, Wall Mounted, Floor**
Housing	**PMMA**
Optic	**Opal PMMA**
Light source	**H.P. LED**
Body dimensions	**Ø 60 mm**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**

Ripple	**3**
Operating voltage	**230 V**
Power factor	**0.96**
Protection rating	**IP68 / IK05**
Lifetime	**>50.000h L80B10**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, COLLAR- 60mm, END CAP NINIO, END FEED NINIO, NINIO BRACKET INOX**

Markings and catalogue references	**CE • LM80**

Options per version

Beams 8° (UN), 13x45° (ASY), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.2 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 13x45°, 25°, 45°	11.2 - 68	**1,128 - 6,548**
930	3000 K	8°, 13x45°, 25°, 45°	11.2 - 68	**1,184 - 6,888**
940	4000 K	8°, 13x45°, 25°, 45°	11.2 - 68	**1,304 - 7,392**

Luminous flux range per version

Minimum 1,128 lm / 11.2 W / 927 / FA0133CL009ON

Maximum 7,392 lm / 68 W / 940 / FA0321CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >