NOXA 2 LED

216 variants



Dimensions



Available colours

White | Black | Grey | Anthracite

NOXA 2 LED is a recessed LED wall luminaire made of aluminium. The body has a length of 190 mm, width of 102 mm and height of 65 mm. Its recessed installation keeps the body within the wall and leaves the light opening visible. It suits paths, entrances and surfaces where lighting needs to form part of the architecture. The light source is an integrated high-power LED module. The opal polycarbonate diffuser creates a luminous surface with a soft appearance. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK08.

LUMINAIRE POWER

1.1 - 4.8 W

LUMINAIRE LUMINOUS FLUX

85 - 390 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOXA 2 LED.

Mounting position	**Wall Recessed**
Housing	**Aluminium**
Optic	**Opal Polycarbonate**
Light source	**H.P. LED**
Body dimensions	**102 × 190 × 65 mm**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**

Ripple	**3**
Power factor	**0.96**
Protection rating	**IP65 / IK08**
Lifetime	**>50.000h L80B10 Module 2x H.P.LED CRI80 Ripple <3%**
Lighting direction	**Sideways**
Accessories	**BOX**

Markings and catalogue references	**CE • LM80**

Options per version

Beams (ASY) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 73.8 - 88.2 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		1.1 - 4.8	**85 - 354**
930	3000 K		1.1 - 4.8	**88 - 363**
940	4000 K		1.1 - 4.8	**97 - 390**

Luminous flux range per version

Minimum 85 lm / 1.1 W / 927 / WF0275CL009ON

Maximum 390 lm / 4.8 W / 940 / WF0292CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >