NUDO DAMA

24 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

NUDO DAMA is a recessed LED wall luminaire made of aluminium. The body has a length of 240 mm, width of 166 mm and height of 130 mm. Its recessed installation keeps the body within the wall and leaves the light opening visible. It suits paths, entrances and surfaces where lighting needs to form part of the architecture. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. The construction is rated IP65 with an impact rating of IK08.

LUMINAIRE POWER

4.2 - 6.3 W

LUMINAIRE LUMINOUS FLUX

232 - 356 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NUDO DAMA.

Mounting position	**Wall Recessed**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP65 / IK08**
Optic	**Safety Glass Clear**	Lifetime	**>50.000h L80B10**
Light source	**H.P. LED**	Lighting direction	**Sideways**
Body dimensions	**166 × 240 × 130 mm**	Accessories	**BOX NUDO**
Ripple	**3**		
Markings and catalogue references	**CE • LM80**		

Options per version

Beams (ASY) | Control On-Off

Luminous efficacy 51.8 - 63.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		4.2 - 6.3	**232 - 324**
930	3000 K		4.2 - 6.3	**240 - 332**
940	4000 K		4.2 - 6.3	**264 - 356**

Luminous flux range per version

Minimum 232 lm / 4.2 W / 927 / WF0305CL009ON

Maximum 356 lm / 6.3 W / 940 / WF0310CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >