
SATIS 2

24 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

SATIS 2 is a recessed LED wall luminaire made of aluminium. The body has a length of 262 mm, width of 262 mm and height of 95 mm. Its recessed installation keeps the body within the wall and leaves the light opening visible. It suits paths, entrances and surfaces where lighting needs to form part of the architecture. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. The construction is rated IP65 with an impact rating of IK07.

LUMINAIRE POWER

5.3 - 8 W

LUMINAIRE LUMINOUS FLUX

120 - 184 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SATIS 2.

Mounting position	**Wall Recessed**	Colour uniformity	**3 SDCM**
Housing	**Aluminium**	Ripple	**3**
Optic	**Safety Glass Clear**	Protection rating	**IP65 / IK07**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10**
Body dimensions	**262 × 262 × 95 mm**	Lighting direction	**Sideways**
Control Gear	**Built-in ECG**	Accessories	**BOX SATIS**
Markings and catalogue references	**CE • LM80**		

Options per version

Control On-Off

Luminous efficacy 20.9 - 25.5 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		5.3 - 8	**120 - 167**
930	3000 K		5.3 - 8	**124 - 171**
940	4000 K		5.3 - 8	**136 - 184**

Luminous flux range per version

Minimum 120 lm / 5.3 W / 927 / WF0324CL009ON

Maximum 184 lm / 8 W / 940 / WF0328CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >