
SOROR 0954

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

SOROR 0954 is an outdoor LED spotlight made of aluminium. The body has a length of 229 mm, width of 120 mm and height of 255 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. The light source is an integrated high-power LED module. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The head offers vertical adjustment through 120°. The optical surface is made of clear safety glass. The available 3.6°–60° beams offer a choice from concentrated accent lighting to wider coverage. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP66 with an impact rating of IK07.

LUMINAIRE POWER

45 - 100 W

LUMINAIRE LUMINOUS FLUX

3,555 - 7,400 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SOROR 0954.

Mounting position	**Ceiling, Wall Mounted, Floor**
Housing	**Aluminium**
Optic	**Safety Glass Clear**
Light source	**H.P. LED**
Body dimensions	**120 × 229 × 255 mm**
Control Gear	**Built-in ECG**

Operating voltage	**230 V**
Protection rating	**IP66 / IK07**
Insulation class	**Class I**
Lifetime	**: 50,000h**
Lighting direction	**Sideways**
Accessories	**ANTI-GLARE, GRILLE, ANTI-GLARE, HOOD, IP68 JUNCTION BOX**

Markings and catalogue references	**CE**

Options per version

Beams 3.6° (UN), 5° (UN), 8° (UN), 15° (N), 20° (N), 30° (M), 40° (W), 45° (W), 60° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 74 - 79 lm/W

Luminous flux range per version

Minimum 3,555 lm / 45 W / PJ0469CL009ON

Maximum 7,400 lm / 100 W / PJ0477CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >