SOROR SQ

56 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

SOROR SQ is an outdoor LED spotlight made of aluminium and silicone. The body has a length of 95 mm, width of 95 mm and height of 142 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. The light source is an integrated high-power LED module. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The head offers vertical adjustment through 90°. The optical surface is made of clear safety glass. The available 5°–60° beams offer a choice from concentrated accent lighting to wider coverage. It is available in anthracite, black, white and grey finishes. The construction is rated IP66 with an impact rating of IK07.

LUMINAIRE POWER

8 - 10 W

LUMINAIRE LUMINOUS FLUX

648 - 740 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SOROR SQ.

Mounting position	**Ceiling, Wall Mounted, Floor**	Operating voltage	**24 V**
Housing	**Aluminium**	Protection rating	**IP66 / IK07**
Optic	**Safety Glass Clear**	Insulation class	**Class III**
Light source	**H.P. LED**	Lighting direction	**Sideways**
Body dimensions	**95 × 95 × 142 mm**	Accessories	**ANTI-GLARE, GRILLE, IP68 JUNCTION BOX**

Markings and catalogue references	**CE**

Options per version

Beams 5° (UN), 8° (UN), 14° (N), 20° (N), 30° (M), 40° (W), 60° (W)

Luminous efficacy 74 - 81 lm/W

Luminous flux range per version

Minimum 648 lm / 8 W / PJ0481CL009

Maximum 740 lm / 10 W / PJ0488CL009

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >