
TALIS 3 BRASS

60 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite** **Uncoloured**

TALIS 3 BRASS is an LED lighting bollard made of brass and aluminium. The body has a diameter of 140 mm. It is offered in 500 and 700 mm heights, allowing the size to be selected for the application. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. The opal PMMA diffuser gives the luminous surface a unified appearance. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white, grey and unpainted finishes. The construction is rated IP65 with an impact rating of IK04.

LUMINAIRE POWER

3.1 - 4.7 W

LUMINAIRE LUMINOUS FLUX

218 - 334 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TALIS 3 BRASS.

Mounting position	**Bollard**	Operating voltage	**230 V**
Housing	**Brass, Aluminium**	Power factor	**0.96**
Optic	**Opal PMMA**	Protection rating	**IP65 / IK04**
Light source	**H.P. LED**	Lighting direction	**Wide spread**
Control Gear	**Remote Electronic Driver**	Accessories	**BRASS NAIL, CONNECTION TOOL 3**
Ripple	**3**		

Markings and catalogue references	**CE**

Options per version

Control On-Off

Luminous efficacy 64.8 - 79.2 lm/W | Height 500 - 700 mm | Diameter 140 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		3.1 - 4.7	**218 - 304**
930	3000 K		3.1 - 4.7	**225 - 311**
940	4000 K		3.1 - 4.7	**248 - 334**

Luminous flux range per version

Minimum 218 lm / 3.1 W / 927 / BO0304CL009ON

Maximum 334 lm / 4.7 W / 940 / BO0314CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >