
# TERES 5 SQUARE STIPO 2

**72 variants**



### Dimensions




### Available colours

**White** **Black** **Grey** **Anthracite**

TERES 5 SQUARE STIPO 2 is an LED lighting bollard made of aluminium. The body has a length of 57 mm, width of 57 mm and height of 515 mm. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP54 with an impact rating of IK05.

**LUMINAIRE POWER**

## 1.1 - 1.7 W

**LUMINAIRE LUMINOUS FLUX**

## 85 - 130 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of TERES 5 SQUARE STIPO 2.

| | | | |
|---|---|---|---|
| Mounting position | **Bollard** | Power factor | **0.96** |
| Housing | **Aluminium** | Protection rating | **IP54 / IK05** |
| Optic | **PMMA** | Lighting direction | **Sideways** |
| Light source | **H.P. LED** | Accessories | **BRASS NAIL** |
| Body dimensions | **57 × 57 × 515 mm** | | |

**Markings and catalogue references** **CE • LM80 • LM79 • TM21 • REACH**

## Options per version

**Beams (W) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 69.4 - 88.2 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **927** | 2700 K | | 1.1 - 1.7 | **85 - 118** |
| **930** | 3000 K | | 1.1 - 1.7 | **88 - 121** |
| **940** | 4000 K | | 1.1 - 1.7 | **97 - 130** |

### Luminous flux range per version

Minimum 85 lm / 1.1 W / 927 / BO0399CL001ON

Maximum 130 lm / 1.7 W / 940 / BO0398CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >