
TERES M1 SMALL B LED

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

TERES M1 SMALL B LED is an outdoor LED wall luminaire made of aluminium. The lighting section has height 155 mm and diameter 105 mm. Wall mounting adds light at entrances, paths beside buildings and exterior walls. The arrangement of fittings can follow the rhythm of the facade and its access points. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. The construction is rated IP65 with an impact rating of IK07.

LUMINAIRE POWER

4.5 - 8.1 W

LUMINAIRE LUMINOUS FLUX

451 - 880 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TERES M1 SMALL B LED.

Mounting position	**Wall Mounted**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**Safety Glass Clear**	Protection rating	**IP65 / IK07**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10 PAR16 / GU10 / 230V**
Body dimensions	**Ø 105 × 155 mm**	Lighting direction	**Sideways**
Ripple	**3**	Accessories	**MOUNTING SET**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (M), 45° (W)

Luminous efficacy 96.3 - 116.5 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	4.5 - 8.1	**451 - 780**
930	3000 K	8°, 25°, 45°	4.5 - 8.1	**474 - 820**
940	4000 K	8°, 25°, 45°	4.5 - 8.1	**522 - 880**

Luminous flux range per version

Minimum 451 lm / 4.5 W / 927 / WF0335CL009

Maximum 880 lm / 8.1 W / 940 / WF0368CL009

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >