
TERES M2 BRASS H.P.LED

270 variants



Dimensions



Available colours

White **Black** **Grey** **Nickel** **Anthracite**

TERES M2 BRASS H.P.LED is an outdoor LED wall luminaire made of brass. The lighting section has height 230 mm and diameter 104 mm. Wall mounting adds light at entrances, paths beside buildings and exterior walls. The arrangement of fittings can follow the rhythm of the facade and its access points. The light source is an integrated high-power LED module. The optical surface is made of clear safety glass. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. Upward and downward emission combines illumination of the space with light on the adjacent surface. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white, grey and nickel finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK07.

LUMINAIRE POWER

11.2 - 16.2 W

LUMINAIRE LUMINOUS FLUX

1,128 - 1,760 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TERES M2 BRASS H.P.LED.

Mounting position	**Wall Mounted**	Ripple	**3**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**Safety Glass Clear**	Protection rating	**IP65 / IK07**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10**
Body dimensions	**Ø 104 × 230 mm**	Accessories	**MOUNTING SET**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.2 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	11.2 - 16.2	**1,128 - 1,559**
930	3000 K	8°, 25°, 45°	11.2 - 16.2	**1,184 - 1,640**
940	4000 K	8°, 25°, 45°	11.2 - 16.2	**1,304 - 1,760**

Luminous flux range per version

Minimum 1,128 lm / 11.2 W / 927 / WF0431CL009ON

Maximum 1,760 lm / 16.2 W / 940 / WF0446CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >