TERES SQUARE STIPO 2 H.P.LED

72 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

TERES SQUARE STIPO 2 H.P.LED is an outdoor LED wall luminaire made of aluminium. The body has a length of 57 mm, width of 57 mm and height of 60 mm. Wall mounting adds light at entrances, paths beside buildings and exterior walls. The arrangement of fittings can follow the rhythm of the facade and its access points. The light source is an integrated high-power LED module. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP54 with an impact rating of IK08.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

85 - 130 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TERES SQUARE STIPO 2 H.P.LED.

Mounting position	**Wall Mounted**	Colour uniformity	**3 SDCM**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**Safety Glass Clear**	Protection rating	**IP54 / IK08**
Light source	**H.P. LED**	Lighting direction	**Sideways**
Body dimensions	**57 × 57 × 60 mm**	Accessories	**MOUNTING SET**
Control Gear	**Built-in ECG**		
Markings and catalogue references	**CE • LM80**		

Options per version

Beams (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 69.4 - 88.2 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		1.1 - 1.7	**85 - 118**
930	3000 K		1.1 - 1.7	**88 - 121**
940	4000 K		1.1 - 1.7	**97 - 130**

Luminous flux range per version

Minimum 85 lm / 1.1 W / 927 / WF0500CL001ON

Maximum 130 lm / 1.7 W / 940 / WF0501CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >