VISO 3 SP MINI 2F

30 variants



Dimensions



Available colours

White **Black** **Grey** **Nickel** **Colourless**

VISO 3 SP MINI 2F is an LED pendant luminaire made of brass. Suspension brings the fitting closer to the area it serves and makes it part of the interior composition. It suits tables, reception areas and seating spaces in homes or hospitality settings. The light source is an integrated high-power LED module. The opal PMMA diffuser gives the luminous surface a unified appearance. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white, grey, nickel and unpainted finishes. The construction is rated IP40 with an impact rating of IK07. Overall horizontal span 197 mm and height 866 mm. The 50 mm diameter refers only to the ceiling canopy.

LUMINAIRE POWER

2.2 - 3.4 W

LUMINAIRE LUMINOUS FLUX

229 - 351 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VISO 3 SP MINI 2F.

Mounting position	**Pendant**	Operating voltage	**230 V**
Housing	**Metal**	Power factor	**0.96**
Light source	**H.P. LED**	Protection rating	**IP40 / IK07**
Body dimensions	**197 × 866 mm**	Insulation class	**Class I**
Control Gear	**Built-in ECG**	Lifetime	**>50.000h L80B10**
Colour uniformity	**3 SDCM**	Lighting direction	**Upwards**
Ripple	**3**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (VW) | Control On-Off

Luminous efficacy 93.8 - 118.6 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		2.2 - 3.4	**229 - 319**
930	3000 K		2.2 - 3.4	**237 - 327**
940	4000 K		2.2 - 3.4	**261 - 351**

Luminous flux range per version

Minimum 229 lm / 2.2 W / 927 / DES0348CL002ON

Maximum 351 lm / 3.4 W / 940 / DES0349CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >