VISO FERUS 55

54 variants



Dimensions



Available colours

Nickel **Uncoloured** **Black stainless steel**

VISO FERUS 55 is an LED luminaire with two arched arms and shades made of brass. The lighting section has height 60 mm and diameter 50 mm. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black stainless steel, nickel and unpainted finishes. The construction is rated IP65 with an impact rating of IK05.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

115 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VISO FERUS 55.

Mounting position	**Bollard**	Ripple	**3**
Housing	**Brass**	Power factor	**0.96**
Light source	**H.P. LED**	Protection rating	**IP65 / IK05**
Body dimensions	**Ø 50 × 60 mm**	Lifetime	**>50.000h L80B10**
Control Gear	**Remote Electronic Driver**	Lighting direction	**Sideways**
Colour uniformity	**3 SDCM**	Accessories	**CONNECTION BOX**
Markings and catalogue references	**CE • LM80**		

Options per version

Beams 8° (N), 25° (M), 45° (W) | Control On-Off

Luminous efficacy 94.1 - 119.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	1.1 - 1.7	**115 - 160**
930	3000 K	8°, 25°, 45°	1.1 - 1.7	**119 - 164**
940	4000 K	8°, 25°, 45°	1.1 - 1.7	**131 - 176**

Luminous flux range per version

Minimum 115 lm / 1.1 W / 927 / BO0414CL151ON

Maximum 176 lm / 1.7 W / 940 / BO0412CL151ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >