
VISO FLEX

108 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite** **Colourless** **Dark brown**

VISO FLEX is an LED lighting bollard made of brass. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The light source is an integrated high-power LED module. PMMA lenses shape the light leaving the LED unit. The available 8°, 25° and 45° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is offered in multiple finishes, including dark brown, anthracite, black and white. The construction is rated IP65 with an impact rating of IK04. The base has a 60 mm diameter and a 120 mm height. The heads have a 20 mm diameter and a 45 mm axial length. The flexible arms allow different configurations.

LUMINAIRE POWER

3.4 - 4.9 W

LUMINAIRE LUMINOUS FLUX

338 - 528 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VISO FLEX.

Mounting position	**Bollard**	Ripple	**3**
Housing	**Brass**	Operating voltage	**230 V**
Optic	**PMMA lenses**	Power factor	**0.96**
Light source	**H.P. LED**	Protection rating	**IP65 / IK04**
Body dimensions	**Ø 60 mm**	Lifetime	**>50.000h L80B10**
Control Gear	**Built-in ECG**	Lighting direction	**Wide spread**
Colour uniformity	**3 SDCM**	Accessories	**BRASS NAIL, CONNECTION TOOL 3**

Markings and catalogue references	**CE • LM80**

Options per version

Beams 8° (UN), 25° (M), 45° (W) | Control On-Off

Luminous efficacy 96.3 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	3.4 - 4.9	**338 - 468**
930	3000 K	8°, 25°, 45°	3.4 - 4.9	**355 - 492**
940	4000 K	8°, 25°, 45°	3.4 - 4.9	**391 - 528**

Luminous flux range per version

Minimum 338 lm / 3.4 W / 927 / BO0424CL152ON

Maximum 528 lm / 4.9 W / 940 / BO0439CL152ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >