
# NINIO 2 OPAL LINEAR LED 3 INOX

**54 variants**



### Dimensions




### Available colours

**Inox**

NINIO 2 OPAL LINEAR LED 3 INOX is a linear LED facade luminaire made of PMMA. The body has a diameter of 60 mm and height of 70 mm. The range offers different lengths, from 370 to 1770 mm, to suit the layout of the space. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The opal PMMA diffuser gives the luminous surface a unified appearance. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. The finish is stainless steel. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP68 with an impact rating of IK05.

**LUMINAIRE POWER**

## 6.4 - 37.8 W

**LUMINAIRE LUMINOUS FLUX**

## 700 - 4,457 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of NINIO 2 OPAL LINEAR LED 3 INOX.

| | |
|---|---|
| Mounting position | **Ceiling, Wall Mounted, Floor** |
| Housing | **PMMA** |
| Optic | **Clear PMMA** |
| Light source | **Linear LED** |
| Body dimensions | **Ø 60 × 70 mm** |
| Control Gear | **Built-in ECG** |
| Colour uniformity | **3 SDCM** |

| | |
|---|---|
| Ripple | **3** |
| Operating voltage | **230 V** |
| Power factor | **0.96** |
| Protection rating | **IP68 / IK05** |
| Lifetime | **>60.000h L70B10** |
| Lighting direction | **Wide spread** |
| Accessories | **AUTO WIRE SUPPORT BLOCK, COLLAR- 60mm, END CAP NINIO, END FEED NINIO, NINIO BRACKET INOX** |

| | |
|---|---|
| **Markings and catalogue references** | **CE • LM80** |

## Options per version

**Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 109.7 - 118.3 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **927** | 2700 K | | 6.4 - 37.8 | **700 - 4,149** |
| **930** | 3000 K | | 6.4 - 37.8 | **725 - 4,303** |
| **940** | 4000 K | | 6.4 - 37.8 | **751 - 4,457** |

### Luminous flux range per version

Minimum 700 lm / 6.4 W / 927 / FA3829CL135ON

Maximum 4,457 lm / 37.8 W / 940 / FA3846CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >