NINIO 4 OPAL LINEAR LED

324 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

NINIO 4 OPAL LINEAR LED is a linear LED facade luminaire made of PMMA. The body has a diameter of 60 mm and height of 120 mm. The range offers different lengths, from 374 to 2474 mm, to suit the layout of the space. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The opal PMMA diffuser gives the luminous surface a unified appearance. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP68 with an impact rating of IK05.

LUMINAIRE POWER

6.4 - 53.7 W

LUMINAIRE LUMINOUS FLUX

700 - 6,319 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NINIO 4 OPAL LINEAR LED.

Mounting position	**Ceiling, Wall Mounted, Floor**
Housing	**PMMA**
Optic	**Opal PMMA**
Light source	**Linear LED**
Body dimensions	**Ø 60 × 120 mm**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**

Ripple	**3**
Operating voltage	**230 V**
Power factor	**0.96**
Protection rating	**IP68 / IK05**
Lifetime	**>60.000h L70B10**
Lighting direction	**Wide spread**
Accessories	**END CAP NINIO, END FEED NINIO, NINIO SIDE COMPONENT**

Markings and catalogue references	**CE • LM80**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 109.6 - 118.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		6.4 - 53.7	**700 - 5,881**
930	3000 K		6.4 - 53.7	**725 - 6,100**
940	4000 K		6.4 - 53.7	**751 - 6,319**

Luminous flux range per version

Minimum 700 lm / 6.4 W / 927 / FA3847CL009ON

Maximum 6,319 lm / 53.7 W / 940 / FA3873CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >