CAVUS 2

54 variants



Dimensions



Available colours

White Black Gold

CAVUS 2 is an LED wall luminaire made of brass, aluminium and steel. The lighting section has height 1230 mm and diameter 40 mm. It adds a wall lighting point in homes, hotels and reception spaces. It complements the main lighting and draws attention to the area where it is installed. The opal PMMA diffuser gives the luminous surface a unified appearance. Upward and downward emission combines illumination of the space with light on the adjacent surface. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white and gold finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP40 with an impact rating of IK06.

LUMINAIRE POWER

12.3 - 19.2 W

LUMINAIRE LUMINOUS FLUX

1,019 - 1,722 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of CAVUS 2.

Mounting position	**Wall Mounted**	Control Gear	**Remote Electronic Driver**
Housing	**Brass, Aluminium, Steel**	Operating voltage	**230 V**
Optic	**Opal PMMA**	Power factor	**0.96**
Light source	**LED Strip**	Protection rating	**IP40 / IK06**
Body dimensions	**Ø 40 × 1230 mm**	Lifetime	**: >50.000h | L80B10 | Energy Saving A+**

Markings and catalogue references	**CE**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 82.9 - 89.6 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		12.3 - 19.2	**1,019 - 1,593**
930	3000 K		12.3 - 19.2	**1,061 - 1,657**
940	4000 K		12.3 - 19.2	**1,102 - 1,722**

Luminous flux range per version

Minimum 1,019 lm / 12.3 W / 927 / DEW0153CL002ON

Maximum 1,722 lm / 19.2 W / 940 / DEW0158CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >