COMIS 10 ASYMMETRIC

18 variants



Dimensions



Available colours

White **Black** **Anodized grey**

COMIS 10 ASYMMETRIC is a linear LED lighting profile made of aluminium. The body has a length of 1000 mm, width of 30 mm and height of 31.85 mm. Its linear construction can create lines of light in homes, workplaces and hospitality interiors. Length and mounting arrangement are selected to suit the surface or route that needs illumination. The optical surface is made of PMMA. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. Available in matte white, matte black and anodized grey. The construction is rated IP40 with an impact rating of IK05. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

10 - 15.6 W

LUMINAIRE LUMINOUS FLUX

592 - 1,000 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 10 ASYMMETRIC.

Mounting position	**Trimless**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK05**
Optic	**PMMA**	Lifetime	**: >50.000h | L80B10 | Energy Saving A+**
Light source	**LED Strip**	Lighting direction	**Sideways**
Body dimensions	**30 × 1000 × 31.85 mm**	Accessories	**DOUBLE SATIN, COVER**
Control Gear	**Remote Electronic Driver**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Control On-Off

Luminous efficacy 59.2 - 64 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		10 - 15.6	**592 - 925**
930	3000 K		10 - 15.6	**616 - 963**
940	4000 K		10 - 15.6	**640 - 1,000**

Luminous flux range per version

Minimum 592 lm / 10 W / 927 / PRT0642CL001ON

Maximum 1,000 lm / 15.6 W / 940 / PRT0647CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >