
COMIS RING BASE

36 variants



Dimensions



Available colours

White **Black** **Anodized grey**

COMIS RING BASE is a surface-mounted LED ceiling luminaire made of aluminium. The ring profile has a height of 16.6 mm. The range offers different diameters, from 600 to 1200 mm, to suit the layout of the space. It mounts directly on the ceiling, leaving the body visible within the room. It suits homes, hospitality interiors and commercial spaces. The optical surface is made of PMMA. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in matte white, matte black and anodized grey finishes. The construction is rated IP40 with an impact rating of IK05. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

23 - 45 W

LUMINAIRE LUMINOUS FLUX

1,495 - 3,377 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS RING BASE.

Mounting position	**Ceiling**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**LED Strip**
Control Gear	**Built-in ECG**

Power factor	**0.96**
Protection rating	**IP40 / IK05**
Lifetime	**>50.000h L70B50 | LM80 test report 30 LED/m**
Lighting direction	**Wide spread**
Accessories	**AUTO WIRE SUPPORT BLOCK, DOUBLE SATIN, COVER, LINEAR OPAL, COVER, LENS SPOT, COVER**

Markings and catalogue references	**CE • LM80**

Options per version

Control On-Off

Luminous efficacy 65 - 75 lm/W | Height 16.6 mm | Diameter 600 - 1,200 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		23 - 45	**1,495 - 2,926**
930	3000 K		23 - 45	**1,610 - 3,151**
940	4000 K		23 - 45	**1,725 - 3,377**

Luminous flux range per version

Minimum 1,495 lm / 23 W / 927 / CM0676CL143ON

Maximum 3,377 lm / 45 W / 940 / CM0672CL143ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >