COMIS STAIRS

54 variants



Dimensions



Available colours

White **Black** **Anodized grey**

COMIS STAIRS is a linear LED stair luminaire made of aluminium. The body has a width of 78.8 mm and height of 95 mm. It is offered in 100, 500 and 1000 mm lengths, allowing the size to be selected for the application. The linear form allows the lighting to follow the geometry of the staircase. Its position is coordinated with the construction details so that the fitting becomes part of the route. The opal polycarbonate diffuser creates a luminous surface with a soft appearance. Upward and downward emission combines illumination of the space with light on the adjacent surface. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anodized grey, black and white finishes. The construction is rated IP20. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

2 - 31.3 W

LUMINAIRE LUMINOUS FLUX

118 - 2,000 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS STAIRS.

Mounting position	**Wall Mounted**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20**
Optic	**Opal Polycarbonate**	Insulation class	**Class II**
Light source	**LED Strip**	Lifetime	**: >50.000h | L80B10 | Energy Saving A+**
Markings and catalogue references	**CE**		

Options per version

Luminous efficacy 59 - 64 lm/W | Length 100 - 1,000 mm | Width 78.8 mm | Height 95 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		2 - 31.3	**118 - 1,850**
930	3000 K		2 - 31.3	**123 - 1,925**
940	4000 K		2 - 31.3	**128 - 2,000**

Luminous flux range per version

Minimum 118 lm / 2 W / 927 / DEW0171CL143

Maximum 2,000 lm / 31.3 W / 940 / DEW0188CL143

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >