MINI NINIO LED

54 variants



Dimensions



MINI NINIO LED is a linear LED facade luminaire made of polycarbonate. The body has a diameter of 15.8 mm. It is offered in 100, 500 and 1000 mm lengths, allowing the size to be selected for the application. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP68 with an impact rating of IK05.

LUMINAIRE POWER

1 - 15.6 W

LUMINAIRE LUMINOUS FLUX

107 - 1,800 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MINI NINIO LED.

Mounting position	**Ceiling, Wall Mounted, Floor**	Power factor	**0.96**
Housing	**PMMA**	Protection rating	**IP68 / IK05**
Light source	**LED Strip**	Lifetime	**: >50.000h | L80B10 | Energy Saving A+**
Body dimensions	**Ø 15.8 mm**	Lighting direction	**Wide spread**
Control Gear	**Remote Electronic Driver**		

Markings and catalogue references **CE**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 106.5 - 115.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		1 - 15.6	**107 - 1,665**
930	3000 K		1 - 15.6	**111 - 1,733**
940	4000 K		1 - 15.6	**115 - 1,800**

Luminous flux range per version

Minimum 107 lm / 1 W / 927 / FA3874ON

Maximum 1,800 lm / 15.6 W / 940 / FA3891ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >