MULTUS 2

204 variants



Dimensions



Available colours

Black **Anthracite** **Anodized grey** **Dark brown**

MULTUS 2 is a linear LED facade luminaire made of aluminium. The body has a length of 1200 mm, width of 42 mm and height of 66 mm. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The optical surface is made of clear safety glass. The available 5°–60° beams offer a choice from concentrated accent lighting to wider coverage. The 10x30°, 10x55° and 8x10° oval distribution provides elongated coverage for surfaces and routes with a matching geometry. The 2700, 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in anodized grey, dark brown, anthracite and black finishes. The construction is rated IP67 with an impact rating of IK10.

LUMINAIRE POWER

36 - 60 W

LUMINAIRE LUMINOUS FLUX

3,420 - 4,920 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MULTUS 2.

Mounting position	**Ceiling, Wall Mounted, Floor**	Operating voltage	**230 V**
Housing	**Aluminium**	Protection rating	**IP67 / IK10**
Optic	**Safety Glass Clear**	Insulation class	**Class I**
Light source	**LED Strip**	Lifetime	**: L70 B10 200.000h**
Body dimensions	**42 × 1200 × 66 mm**	Lighting direction	**Upwards**
Control Gear	**Built-in ECG**		
Markings and catalogue references	**CE**		

Options per version

Beams 5° (UN), 8° (UN), 8x10° (ASY), 10° (UN), 10x30° (ASY), 10x55° (ASY), 14° (N), 16° (N), 20° (N), 25° (M), 30° (M), 40° (W), 60° (W) | Control On-Off

Luminous efficacy 72 - 105 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
827	2700 K	5°, 8°, 8x10°, 10°, 10x30°, 10x55°, 14°, 16°, 20°, 25°, 30°, 40°, 60°	36 - 60	**3,420 - 4,320**
830	3000 K	5°, 8°, 8x10°, 10°, 10x30°, 10x55°, 14°, 16°, 20°, 25°, 30°, 40°, 60°	36 - 60	**3,600 - 4,620**
840	4000 K	5°, 8°, 8x10°, 10°, 10x30°, 10x55°, 14°, 16°, 20°, 25°, 30°, 40°, 60°	36 - 60	**3,780 - 4,920**

Luminous flux range per version

Minimum 3,420 lm / 36 W / 827 / FA3892CL143ON

Maximum 4,920 lm / 60 W / 840 / FA3915CL143ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >