
NINIO S

270 variants



Dimensions



Available colours

White **Black** **Grey**

NINIO S is a linear LED facade luminaire made of polycarbonate. The body has a diameter of 38 mm. The range offers different lengths, from 100 to 2000 mm, to suit the layout of the space. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The opal PMMA diffuser gives the luminous surface a unified appearance. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP54 with an impact rating of IK06.

LUMINAIRE POWER

1.1 - 35 W

LUMINAIRE LUMINOUS FLUX

89 - 3,185 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NINIO S.

Mounting position	**Ceiling, Wall Mounted, Floor**	Control Gear	**Remote Electronic Driver**
Housing	**PMMA**	Power factor	**0.96**
Optic	**Opal PMMA**	Protection rating	**IP54 / IK06**
Light source	**LED Strip**	Lifetime	**: >50.000h | L80B10 | Energy Saving A+**
Body dimensions	**Ø 38 mm**	Lighting direction	**Upwards**

Markings and catalogue references	**CE**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 81.4 - 96.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		1.1 - 35	**89 - 2,850**
930	3000 K		1.1 - 35	**95 - 3,025**
940	4000 K		1.1 - 35	**102 - 3,185**

Luminous flux range per version

Minimum 89 lm / 1.1 W / 927 / FA3958CL001ON

Maximum 3,185 lm / 35 W / 940 / FA3957CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >