VOCO 2 WALL

216 variants



Dimensions



Available colours

White	Black	Grey	Chocolat	Olive	Sand	Bordeaux	520 Helios	530 Selene	581 Kronos	582 Perseus	586 Gaea

VOCO 2 WALL is an LED wall luminaire made of ceramic. The body has a length of 400 mm and height of 270 mm. It adds a wall lighting point in homes, hotels and reception spaces. It complements the main lighting and draws attention to the area where it is installed. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is offered in multiple finishes, including chocolat, black, white and grey. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project.

LUMINAIRE POWER

6.6 - 9.9 W

LUMINAIRE LUMINOUS FLUX

828 - 1,339 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VOCO 2 WALL.

Mounting position	**Wall Mounted**	Control Gear	**Remote Electronic Driver**
Housing	**Ceramic**	Operating voltage	**230 V**
Light source	**LED Strip**	Lifetime	**: >50.000h | L80B10 | Energy Saving A+**
Body dimensions	**400 × 270 mm**	Lighting direction	**Wide spread**
Markings and catalogue references	**CE**		

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 124.8 - 140 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		6.6 - 9.9	**828 - 1,240**
930	3000 K		6.6 - 9.9	**861 - 1,290**
940	4000 K		6.6 - 9.9	**927 - 1,339**

Luminous flux range per version

Minimum 828 lm / 6.6 W / 927 / DEK0106CL116ON

Maximum 1,339 lm / 9.9 W / 940 / DEK0111CL116ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >