
SOLUS 2

320 variants



Dimensions



Available colours

White Black Grey Anthracite

SOLUS 2 is an outdoor LED spotlight made of aluminium. The body has a diameter of 210 mm and height of 58 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The head offers vertical adjustment through 170°. The available 20°, 60° and 100° beams offer a choice from concentrated accent lighting to wider coverage. The 30x115° oval distribution provides elongated coverage for surfaces and routes with a matching geometry. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK08.

LUMINAIRE POWER

7.5 - 23 W

LUMINAIRE LUMINOUS FLUX

1,070 - 3,150 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SOLUS 2.

Mounting position	**Ceiling, Wall Mounted, Floor**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Colour uniformity	**3 SDCM**
Light source	**SMD LED**	Ripple	**3**
Body dimensions	**Ø 210 × 58 mm**	Protection rating	**IP65 / IK08**
Markings and catalogue references	**CE**		

Options per version

Beams 20° (N), 30x115° (ASY), 60° (W), 100° (VW) | Control On-Off, DALI2

Luminous efficacy 129.6 - 150.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	20°, 30x115°, 60°, 100°	7.5 - 23	**1,070 - 2,980**
840	4000 K	20°, 30x115°, 60°, 100°	7.5 - 23	**1,130 - 3,150**

Luminous flux range per version

Minimum 1,070 lm / 7.5 W / 830 / PJ0519CL009ON

Maximum 3,150 lm / 23 W / 840 / PJ0554CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >