
TERES M7 SQUARE HEAVY WALL

320 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

TERES M7 SQUARE HEAVY WALL is an outdoor LED wall luminaire made of aluminium. The luminaire body measures 600 × 98 × 98 mm (length × width × height). Wall mounting adds light at entrances, paths beside buildings and exterior walls. The arrangement of fittings can follow the rhythm of the facade and its access points. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP66 with an impact rating of IK07.

LUMINAIRE POWER

12.8 - 41.8 W

LUMINAIRE LUMINOUS FLUX

1,800 - 5,100 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TERES M7 SQUARE HEAVY WALL.

Mounting position	**Wall Mounted**	Colour uniformity	**3 SDCM**
Housing	**Aluminium**	Ripple	**3**
Light source	**SMD LED**	Protection rating	**IP66 / IK07**
Body dimensions	**98 × 600 × 98 mm**	Accessories	**MOUNTING SET**
Control Gear	**Built-in ECG**		

Markings and catalogue references **CE**

Options per version

Beams (II), (III), (V), (ASY) | Control On-Off, DALI2

Luminous efficacy 114.8 - 148.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K		12.8 - 41.8	**1,800 - 4,800**
840	4000 K		12.8 - 41.8	**1,900 - 5,100**

Luminous flux range per version

Minimum 1,800 lm / 12.8 W / 830 / WF0505CL009ON

Maximum 5,100 lm / 41.8 W / 840 / WF0540CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >