TERES M7 URBAN 2F

832 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

TERES M7 URBAN 2F is an LED amenity luminaire made of aluminium. Each head measures 600 × 98 × 98 mm (length × width × height). The pole is available in heights from 4,500 to 6,000 mm. Pole mounting supports lighting layouts for squares, pedestrian routes and shared outdoor areas. Power, distribution and spacing are selected as part of the lighting design for the particular site. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP66 with an impact rating of IK10.

LUMINAIRE POWER

20 - 80 W

LUMINAIRE LUMINOUS FLUX

2,626 - 12,764 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TERES M7 URBAN 2F.

Mounting position	**Pole Mounted**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Colour uniformity	**3 SDCM**
Light source	**SMD LED**	Protection rating	**IP66 / IK10**
Body dimensions	**30 × 180 × 10 mm**	Accessories	**ANCHOR STOPPER, POLE BASE**
Markings and catalogue references	**CE**		

Options per version

Beams (III), (ASY), (I), (II), (V), (IV) | Control On-Off, DALI2

Luminous efficacy 131.3 - 159.6 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K		20 - 80	**2,626 - 11,964**
840	4000 K		20 - 80	**2,826 - 12,764**

Luminous flux range per version

Minimum 2,626 lm / 20 W / 830 / AM0696CL001ON

Maximum 12,764 lm / 80 W / 840 / AM0779CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >