BARO 2

729 variants



Dimensions



Available colours

White Black Grey

BARO 2 is an LED track spotlight made of aluminium. The body has a diameter of 90 mm and height of 128 mm. Track installation suits shops, display spaces and homes where lighting positions follow the arrangement of objects and surfaces. The light source is an integrated COB LED module. The head offers vertical adjustment through 90° and horizontal adjustment through 360°. The available 10°, 23° and 36° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK07.

LUMINAIRE POWER

11.2 - 27.4 W

LUMINAIRE LUMINOUS FLUX

1,264 - 3,071 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BARO 2.

Mounting position	**Track**	Colour uniformity	**3 SDCM**
Housing	**Aluminium**	Ripple	**3**
Light source	**COB LED**	Operating voltage	**230 V**
Body dimensions	**Ø 90 × 128 mm**	Power factor	**0.96**
Control Gear	**Built-in ECG**	Protection rating	**IP20 / IK07**

Markings and catalogue references	**CE**

Options per version

Beams 10° (UN), 23° (M), 36° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 101 - 124.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	10°, 23°, 36°	11.2 - 27.4	**1,264 - 2,767**
930	3000 K	10°, 23°, 36°	11.2 - 27.4	**1,320 - 2,904**
940	4000 K	10°, 23°, 36°	11.2 - 27.4	**1,390 - 3,071**

Luminous flux range per version

Minimum 1,264 lm / 11.2 W / 927 / SP1761CL002ON

Maximum 3,071 lm / 27.4 W / 940 / SP1839CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >