CERVA 7

9 variants



Dimensions



Available colours

Dark Grey

CERVA 7 is an outdoor LED spotlight made of aluminium. The lighting section has length 106 mm and diameter 62 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. The light source is an integrated COB LED module. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The head offers vertical adjustment through 90°. The available 15°, 24° and 36° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. The finish is dark grey. The construction is rated IP67.

LUMINAIRE POWER

7 W

LUMINAIRE LUMINOUS FLUX

339 - 409 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of CERVA 7.

Mounting position	**Ceiling, Wall Mounted, Floor**	Operating voltage	**24 V**
Housing	**Aluminium**	Protection rating	**IP67**
Light source	**COB LED**	Insulation class	**Class II**
Body dimensions	**Ø 62 mm**	Accessories	**HONEY COMB**
Control Gear	**Remote Electronic Driver**		

Markings and catalogue references	**CE**

Options per version

Beams 15° (N), 24° (M), 36° (W) | Control On-Off

Luminous efficacy 48.4 - 58.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 24°, 36°	7	**339**
930	3000 K	15°, 24°, 36°	7	**374**
940	4000 K	15°, 24°, 36°	7	**409**

Luminous flux range per version

Minimum 339 lm / 7 W / 927 / PJ0595CL103ON

Maximum 409 lm / 7 W / 940 / PJ0601CL103ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >