# MINOR 1F LED

**1,008 variants**



## Dimensions




## Available colours

White Black Grey

MINOR 1F LED is a recessed LED ceiling luminaire made of steel and aluminium. The body has a length of 199 mm, width of 199 mm and height of 155 mm. Its recessed installation keeps the room free of projecting fittings and suits homes, hospitality interiors and commercial spaces that call for a clean ceiling. The light source is an integrated COB LED module. The head offers vertical adjustment through 30° and horizontal adjustment through 30°. The optical surface is made of clear polycarbonate. The available 15°, 24°, 40° and 60° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK07.

**LUMINAIRE POWER**

12.1 - 43.8 W

**LUMINAIRE LUMINOUS FLUX**

1,397 - 5,031 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr >**

# Technical characteristics

## Common data

Characteristics that apply to all versions of MINOR 1F LED.

| | |
|---|---|
| Mounting position | **Ceiling Recessed** |
| Housing | **Metal** |
| Optic | **PMMA** |
| Light source | **COB LED** |
| Body dimensions | **199 × 199 × 155 mm** |

| | |
|---|---|
| Control Gear | **Remote Electronic Driver** |
| Colour uniformity | **3 SDCM** |
| Ripple | **3** |
| Protection rating | **IP20 / IK07** |
| Accessories | **SHADE R111, WALL WASHER, RGB CONTROLLER** |

**Markings and catalogue references** **CE • LM80 • LM79 • TM21 • REACH**

## Options per version

**Beams 15° (N), 24° (M), 40° (W), 60° (W) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 100.5 - 126.8 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **927** | 2700 K | 15°, 24°, 40°, 60° | 12.1 - 43.8 | **1,397 - 4,581** |
| **930** | 3000 K | 15°, 24°, 40°, 60° | 12.1 - 43.8 | **1,458 - 4,800** |
| **935** | 3500 K | 15°, 24°, 40°, 60° | 12.1 - 43.8 | **1,495 - 4,915** |
| **940** | 4000 K | 15°, 24°, 40°, 60° | 12.1 - 43.8 | **1,532 - 5,031** |

### Luminous flux range per version

Minimum 1,397 lm / 12.1 W / 927 / DL5419CL002ON

Maximum 5,031 lm / 43.8 W / 940 / DL5499CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >