
MOBILIS SQUARE LED

1,890 variants



Dimensions



Available colours

White | Black | Grey | Gold | Chrome | Nickel

MOBILIS SQUARE LED is a recessed LED ceiling luminaire made of aluminium. The body has a length of 95 mm, width of 95 mm and height of 112 mm. Its recessed installation keeps the room free of projecting fittings and suits homes, hospitality interiors and commercial spaces that call for a clean ceiling. The light source is an integrated COB LED module. The head offers vertical adjustment through 30°. Its square face gives it a distinct presence in the ceiling and complements straight architectural lines. The optical surface is made of clear safety glass. The available 18°, 24°, 36° and 60° beams offer a choice from concentrated accent lighting to wider coverage. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is offered in multiple finishes, including black, white, grey and gold. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK03.

LUMINAIRE POWER

6 - 10.8 W

LUMINAIRE LUMINOUS FLUX

655 - 1,151 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MOBILIS SQUARE LED.

Mounting position	**Ceiling Recessed**	Control Gear	**Remote Electronic Driver**
Housing	**Aluminium**	Ripple	**3**
Light source	**COB LED**	Protection rating	**IP20 / IK03**
Body dimensions	**95 × 95 × 112 mm**	Insulation class	**Class III**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 101 - 115.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**655 - 1,091**
935	3500 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**674 - 1,121**
940	4000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**692 - 1,151**

Luminous flux range per version

Minimum 655 lm / 6 W / 930 / DL5503CL002ON

Maximum 1,151 lm / 10.8 W / 940 / DL5516CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >