
PENDO 2 IP65 CEILING LED

288 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

PENDO 2 IP65 CEILING LED is an outdoor surface-mounted LED ceiling luminaire made of aluminium. The body has a diameter of 120 mm and height of 320 mm. Ceiling mounting suits entrances and covered outdoor areas. The visible body forms part of the design and allows distinct lighting points to be arranged across the space. The light source is an integrated COB LED module. The optical surface is made of clear safety glass. The available 18°, 24°, 36° and 60° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK07.

LUMINAIRE POWER

12.8 - 18.7 W

LUMINAIRE LUMINOUS FLUX

1,377 - 2,106 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of PENDO 2 IP65 CEILING LED.

Mounting position	**Ceiling**	Body dimensions	**Ø 120 × 320 mm**
Housing	**Aluminium**	Ripple	**3**
Optic	**Safety Glass Clear**	Protection rating	**IP65 / IK07**
Light source	**COB LED**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 102.2 - 118.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	18°, 24°, 36°, 60°	12.8 - 18.7	**1,377 - 1,911**
930	3000 K	18°, 24°, 36°, 60°	12.8 - 18.7	**1,441 - 2,004**
940	4000 K	18°, 24°, 36°, 60°	12.8 - 18.7	**1,514 - 2,106**

Luminous flux range per version

Minimum 1,377 lm / 12.8 W / 927 / CM0701CL009ON

Maximum 2,106 lm / 18.7 W / 940 / CM0688CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >