
POTIS S LED

756 variants



Dimensions



Available colours

White **Black** **Grey**

POTIS S LED is an LED track spotlight made of aluminium. The lighting section has length 128 mm and diameter 54 mm. Track installation suits shops, display spaces and homes where lighting positions follow the arrangement of objects and surfaces. The light source is an integrated COB LED module. The head offers vertical adjustment through 90° and horizontal adjustment through 360°. The optical surface is made of clear safety glass. The available 17°, 24° and 36° beams offer a choice from concentrated accent lighting to wider coverage. The 3000, 3500 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK05.

LUMINAIRE POWER

4 - 10.4 W

LUMINAIRE LUMINOUS FLUX

420 - 1,118 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of POTIS S LED.

Mounting position	**Track, Ceiling**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Colour uniformity	**3 SDCM**
Optic	**Safety Glass Clear**	Ripple	**3**
Light source	**COB LED**	Operating voltage	**230 V**
Body dimensions	**Ø 54 mm**	Protection rating	**IP20 / IK05**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 17° (N), 24° (NM), 36° (M) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.5 - 116.5 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	17°, 24°, 36°	4 - 10.4	**420 - 1,004**
930	3000 K	17°, 24°, 36°	4 - 10.4	**440 - 1,056**
935	3500 K	17°, 24°, 36°	4 - 10.4	**458 - 1,100**
940	4000 K	17°, 24°, 36°	4 - 10.4	**466 - 1,118**

Luminous flux range per version

Minimum 420 lm / 4 W / 927 / SP2051CL002ON

Maximum 1,118 lm / 10.4 W / 940 / SP1876CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >