# RAMUS

**24 variants**



## Dimensions




## Available colours

**White** **Black**

RAMUS is a recessed LED ceiling luminaire made of aluminium. The body has a diameter of 140 mm and height of 110 mm. Its recessed installation keeps the room free of projecting fittings and suits homes, hospitality interiors and commercial spaces that call for a clean ceiling. The light source is an integrated COB LED module. The head offers vertical adjustment through 30° and horizontal adjustment through 360°. The optical surface is made of clear polycarbonate. The available 15°, 24°, 40° and 60° beams offer a choice from concentrated accent lighting to wider coverage. Light at 4000 K with CRI90 supports faithful colour rendering of materials and objects. It is available in black and white finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK04.

**LUMINAIRE POWER**

23 W

**LUMINAIRE LUMINOUS FLUX**

2,393 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr >**

# Technical characteristics

## Common data

Characteristics that apply to all versions of RAMUS.

| | | | |
|---|---|---|---|
| Mounting position | **Ceiling Recessed** | Body dimensions | **Ø 140 × 110 mm** |
| Housing | **Aluminium** | Control Gear | **Remote Electronic Driver** |
| Optic | **Clear Polycarbonate** | Operating voltage | **230 V** |
| Light source | **COB LED** | Protection rating | **IP20 / IK04** |
| **Markings and catalogue references** | **CE** | | |

## Options per version

**Beams 15° (N), 24° (M), 40° (W), 60° (W) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 104 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **940** | 4000 K | 15°, 24°, 40°, 60° | 23 | **2,393** |

### Luminous flux range per version

Minimum 2,393 lm / 23 W / 940 / DL5573CL002ON

Maximum 2,393 lm / 23 W / 940 / DL5573CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr >**