
RITUS 70 ASYMMETRIC

18 variants



Dimensions



Available colours

White **Black**

RITUS 70 ASYMMETRIC is a recessed LED ceiling luminaire made of aluminium. The body has a diameter of 80 mm and height of 71 mm. Its recessed installation keeps the room free of projecting fittings and suits homes, hospitality interiors and commercial spaces that call for a clean ceiling. The light source is an integrated COB LED module. The 3000, 3500 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP54 with an impact rating of IK04. IP54 protection for recessed ceiling installation.

LUMINAIRE POWER

10 W

LUMINAIRE LUMINOUS FLUX

480 - 504 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of RITUS 70 ASYMMETRIC.

Mounting position	**Ceiling Recessed**	Control Gear	**Remote Electronic Driver**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**COB LED**	Protection rating	**IP54 / IK04**
Body dimensions	**Ø 80 × 71 mm**	Lighting direction	**Sideways**
Markings and catalogue references	**CE**		

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 48 - 50.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		10	**480**
935	3500 K		10	**492**
940	4000 K		10	**504**

Luminous flux range per version

Minimum 480 lm / 10 W / 930 / DL5584CL002ON

Maximum 504 lm / 10 W / 940 / DL5585CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >