RITUS 70 SPOT

90 variants



Dimensions



Available colours

White **Black**

RITUS 70 SPOT is a recessed LED ceiling luminaire made of aluminium and plastic. The body has a diameter of 85 mm and height of 100 mm. Its recessed installation keeps the room free of projecting fittings and suits homes, hospitality interiors and commercial spaces that call for a clean ceiling. The light source is an integrated COB LED module. The head offers vertical adjustment through 90° and horizontal adjustment through 360°. The available 10°–50° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP54 with an impact rating of IK04. Suitable for recessed installation in outdoor ceilings, with IP54 protection.

LUMINAIRE POWER

4.8 W

LUMINAIRE LUMINOUS FLUX

376 - 424 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of RITUS 70 SPOT.

Mounting position	**Ceiling Recessed**	Colour uniformity	**3 SDCM**
Housing	**Aluminium**	Ripple	**3**
Light source	**COB LED**	Protection rating	**IP54 / IK04**
Body dimensions	**Ø 85 × 100 mm**	Accessories	**HONEY COMB**
Control Gear	**Remote Electronic Driver**		

Markings and catalogue references **CE**

Options per version

Beams 10° (UN), 15° (N), 24° (M), 36° (W), 50° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 78.3 - 88.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	10°, 15°, 24°, 36°, 50°	4.8	**376**
930	3000 K	10°, 15°, 24°, 36°, 50°	4.8	**400**
940	4000 K	10°, 15°, 24°, 36°, 50°	4.8	**424**

Luminous flux range per version

Minimum 376 lm / 4.8 W / 927 / DL5598CL002ON

Maximum 424 lm / 4.8 W / 940 / DL5608CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >